

# IC SOCKET 2.54mm(0.100") - PITCH=7.62mm

**ASSMANN**  
Electronic Components

## Specifications

Contact Resistance:  $\leq 30m$  max. at DC 100mA

Insulator Resistance: 1000M min. at DC 500V

Current Rating: 1 AMP

Dielectric Withstanding

Voltage: AC 500V For 1 minute


Operating Temperature:  $-55^{\circ}\sim+105^{\circ}c$

Contact: Phosphor Bronze


Housing: PBT & 30% Glass Fiber (UL 94V-0)

Axx-LC-TR-R

# OF CONTACTS



RoHS COMPLIANT



## Dimension

Position	A	B
6	5.08	7.62
8	7.62	10.16
14	15.24	17.78
16	17.78	20.32
18	20.32	22.86
*20	22.86	25.4
22	25.4	27.94

一般公差	.00	$\pm 0.05$	.0	$\pm 0.1$	0.	$\pm 0.3$	10-29.99	$\pm 0.5$
30-99.99	$\pm 1.0$	100-299.99	$\pm 1.5$	品名	IC SOCKET 2.54mm(0.100") - PITCH=7.62mm			
Axx-LC-TR-R		比例	4/1	投影	第三角法	圖樣編號	承認	
		單位	mm	繪圖	張 開驗	日 期	2003/08/30	版本 A